



ANTI-FOG
OPTIONS



H2MAX
OPTIONS



DIELECTRIC



LOCKING
TEMPLE



CUSTOM
LOGO

TruLock™

ANSI/ISEA Z87.1-2020 + | CAN/CSA Z94.3-2020 | CE/UKCA EN 166

Dielectric // Lightweight spectacle – 21 gm // Patented temples lock into place // Custom imprinting available

VARIATIONS

Black Temples | 4 Variations

- SB9510S Clear
- SB9510ST Clear **H2X** AF
- SB9520ST Gray **H2X** AF
- SB9580ST I/O Mirror AF

i I/O Mirror AF does not meet the specified dielectric properties.



TruLock™ Multi-Colors

ANSI/ISEA Z87.1-2020 + | CAN/CSA Z94.3-2020 | CE/UKCA EN 166

Sold in dozen quantity only // Comes with six assorted temple colors: red, blue, green, purple, orange and black / Multi-pack includes two of each temple color // Perfect for work areas where color coding is necessary // Custom imprinting available

VARIATION

Multi-Color Temples | 1 Variation

- S9510SMP Clear



Part No.	Lens Marking	Temple Marking
SB9510S	P Z87 + U6	P Z87 + / P c SEI Z94.3
SB9510ST	P Z87 + U6	P Z87 + / P c SEI Z94.3
SB9520ST	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3
SB9580ST	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3
S9510SMP	P Z87 + U6	P Z87 + / P c SEI Z94.3

General Specifications	Materials
Weight: 21 gm	Lens: Polycarbonate
Bridge: 11.3 Curve	Temples: Nylon
Lens Base: 9.5 Curve	Hinge: Nylon
Lens Size Diagonal: 132.7mm	
Lens Size Vertical: 44 mm	
Lens Thickness: 1.8 mm	
Overall Length (lens - tip): 157 mm	
Overall Width (hinge - hinge): 130 mm	

Lens Marking Symbols

P: Manufacturer's Mark
 Z87: ANSI Standard for Eye and Face Protection Devices
 +: High Impact
 S: Special Purpose
 UV Filter Transmittance
 U6: .01% Max Effective Far UV • .1% Max Near UV

Visible Light Filters

L1.7: 55% Max. Visible Light
 L2.5: 29% Max. Visible Light

Temple Marking Symbols

P: Manufacturer's Mark
 Z87: ANSI Standard for Eye and Face Protection Devices
 +: High Impact
 Z94.3: CAN/CSA Standard for Eye and Face Protection Devices

Product markings may vary //
 Updated as of 11.25