



DIELECTRIC



DUAL PANE LENS



PASSES D3 DROPLET AND SPLASH TEST



BALLISTIC



AIRSOFT

V2G Plus[®]

ANSI/ISEA Z87.1-2020 + | CAN/CSA Z94.3-2020 | CE/UKCA EN 166 | MIL-PRF-32432

Wide adjustable elastic strap with quick-release system creates secure fit // TPU frame provides excellent resistance to cold and heat // Thermo lens system provides excellent resistance to fog caused by temperature differences in your environment // Special indirect ventilation system located at the top and bottom of frame allows airflow and heat release // Multi-functional goggle with 180° vision protects against chemical splash, sun glare, dust, flying particles, and wind // Outer polycarbonate lens protects against the environment while an inner acetate lens prevents fogging // Passes Ballistic MIL-PRF-32432 High Velocity Impact standards // Passes D3: Droplet and Splash Test // Meets ASTM F2879-22 Standard Specification for Eye Protective Devices for Airsoft Sports when worn with strap // Dielectric // Custom imprinting available



VARIATIONS

Black Body with Strap | 2 Variations

- GB6410SDT Clear Dual Pane **H2X AF**
- GB6420SDT Gray Dual Pane **H2X AF**

MATERIALS

Lens	Nose Piece	Foam	Frame	Strap	Strap Holder
Polycarbonate + Acetate	Thermoplastic Polyurethane	Polyurethane	Thermoplastic Polyurethane	Polyester	Polycarbonate

MARKINGS

Part No.	Lens Marking	Temple Marking	Lens Marking Symbols	Temple Marking Symbols	Measurements
GB6410SDT	P Z87 + U6 L1.3 X	P Z87 + D3 / P c SEI Z94.3	P: Manufacturer's Mark Z87: ANSI/ISEA Z87.1-2020 Standard for Eye and Face Protection Devices +: High Impact UV Filter Transmittance U6: .01% Max Effective Far UV • .1% Max Near UV Visible Light Filters L1.3: 85% Max Visible Light L2.5: 29% Max Visible Light	P: Manufacturer's Mark Z87: ANSI/ISEA Z87.1-2020 Standard for Eye and Face Protection Devices +: High Impact D3: Droplet and Splash Test Z94.3: Certified for CAN/CSA Z94.3-20 Standard for Eye and Face Protection Devices	Weight: 80 gm Bridge: 33.5 mm PD: 68 mm Lens Base: 5.5 curve Lens Size Diagonal: 139 mm Lens Size Vertical: 63.5 mm Lens Thickness: 2.1 mm Overall Length (lens - tip): 87 mm Overall Width (hinge - hinge): 136 mm Closest Point Between Lens: 20.3 mm Strap Length: 500 mm
GB6420SDT	P Z87 + U6 L2.5 X	P Z87 + D3 / P c SEI Z94.3			

Product markings may vary // Updated as of 02.26