

V2™ Metal

ANSI/ISEA Z87.1-2020 + | CAN/CSA Z94.3-2020 |
CE/UKCA EN 166

Spring loaded temples allows for easy positioning // Contemporary metal frame and temples fit most facial sizes // Custom imprinting available

VARIATIONS

Gun Metal Frame | 2 Variations

- SGM1810S Clear
- SGM1820S Gray



Part No.	Lens Marking	Frame Marking	General Specifications	Materials
SGM1810S	P Z87 + U6	P Z87 + / P c SEI Z94.3	Weight: 40 gm	Lens: Polycarbonate
SGM1820S	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3	PD: 68 mm	Frame: Copper + Brass Alloy
			Bridge: 8 mm	Temples: Copper + Brass Alloy
			Lens Base: 9.75 Curve	Hinge: Polycarbonate
			Lens Size Diagonal: 85 mm	Screw: Stainless Steel
			Lens Size Vertical: 45.9 mm	Sleeve: Copper + Brass Alloy
			Lens Thickness: 2.2 mm	Nose Piece: Copper + Brass Alloy & Polyvinyl Chloride
			Overall Length (lens - tip): 157 mm	Side Shields: Polycarbonate
			Overall Width (hinge - hinge): 135 mm	
			Closest Point Between Lens: 10.5 mm	

Lens Marking Symbols	Temple Marking Symbols
P: Manufacturer's Mark	P: Manufacturer's Mark
+: High Impact	+: High Impact
Z87: ANSI Standard for Eye and Face Protection Devices	SEI Z94.3: CAN/CSA Standard for Eye and Face Protection Devices
UV Filter Transmittance	
U6: .01% Max Effective Far UV • .1% Max Near UV	
Visible Light Filters	
L2.5: 29% Max Visible Light	

Product markings may vary // Updated as of 07.26