# VENTUREGEAR

## Clandestine™

...

.

E1			$\sim$
Electr	nnic	oarm	11#
LICCU	ULIIC	carm	un

Slim profile ear cups

Height adjustment to fit all sizes

Fold-away, padded headband

Omni directional microphone

Amplifies hearing, while suppressing harmful sounds and reducing them to a safe level

External access for easy battery replacement (2 AAA batteries are included)



## General Specifications

Noise reduction rating (NRR): 24dB Hearing protection style: earmuff Earmuff dimension: 15.5 cm x 15.5 cm x 9.5 cm Earcup thickness: 3.2 mm Weight: 324 gm

#### **Materials**

Headband: polyoxymethylene (POM) Headband cushion: polyurethane (PU) Headband adjustments: acrylonitrile-butadiene-styrene (ABS) Earcup and volume dial: acrylonitrile-butadiene-styrene (ABS) Earcup cushion: polyurethane (PU) Battery compartment: acrylonitrile-butadiene-styrene (ABS)

### **Product Guidelines**

The level of noise entering a person's ear, when hearing protection is worn as directed is approximated by the difference between the A-weighted environmental level and the NRR.

- Example: 1. The environmental noise level at the ear is 92 dB(A).
  - 2. The NRR is 32 decibels (dB).
  - 3. The level of noise entering the ear is approximately equal to 60 dB(A).

CAUTION: For noise environments dominated by frequencies below 500 Hz, the Cweighted environmental noise level should be used. Improper fit of this device will reduce its effectiveness in continuous noise. Plugs should be inserted with a gentle rocking; twisting motion while opposite hand is opening ear canal by pulling the top of ear. Although hearing protectors can be recommended for protection against the harmful effects of impulse noise, the Noise Reduction Rating (NRR) is based on the attenuation noise and may not be an accurate indicator of the protection attainable against impulsive noise, such as gunfire.





857676007617

Black Graphite Pattern Ear Cup with Black Headband

Part No.	UPC	
VGPME10 •	811907028871	
Black Ear Cup with Black Headband		





VGPME17 •





All hearing protection meets ANSI S3.19 standards (•). For more information visit our website or contact your sales representative.



(P) 800.736.8673 | (F) 901.861.4967