



RUBBER
NOSEPIECE



ADJUSTABLE
TEMPLES



MIL-PRF-
32432



READER
OPTION



Venture II®

ANSI/ISEA Z87.1-2020 + | CAN/CSA Z94.3-20 |
CE/UKCA EN 166 | MIL-PRF-32432

Temples adjust to four different lengths // Rubber nosepiece secures the glass and prevents slipping // Passes Ballistic MIL-PRF-32432 High Velocity Impact standards // Custom imprinting available

VARIATIONS

Black Frame | 15 Variations

SB1810S	Clear
SB1810ST	Clear H2X AF
SB1820S	Gray
SB1820ST	Gray H2X AF
SB1830S	Amber
SB1835S	Rust Bronze
SB1840S	Orange
SB1850SF	5.0 IR Filter
SB1860S	Infinity Blue
SB1860SF	3.0 IR Filter
SB1870S	Silver Mirror
SB1875S	Blue Mirror
SB1880S	I/O Mirror
SB1880ST	I/O Mirror AF
SB1890S	Gold Mirror

Metallic Blue Frame | 3 Variations

SMB1810S	Clear
SMB1820S	Gray
SMB1880S	I/O Mirror

Slate Gray Frame | 1 Variation

SSG1810S	Clear
----------	-------



SMB18



SSG18



RUBBER
NOSEPIECE



ADJUSTABLE
TEMPLES



MIL-PRF-
32432



READER
OPTION



Part No.	Lens Marking	Temple Marking	General Specifications	Materials
SB1810S	P + U6	P Z87 + / P c SEI Z94.3	Weight: 27 gm	Lens: polycarbonate
SB1810ST	P + U6	P Z87 + / P c SEI Z94.3	PD: 68 mm	Frame: nylon 6-6 - poly(hexamethylene adipamide)
SB1820S	P + U6 L 2.5	P Z87 + / P c SEI Z94.3	Bridge: 10.5 mm	Temples: polycarbonate & thermoplastic elastomers (TPE)
SB1820ST	P + U6 L 2.5	P Z87 + / P c SEI Z94.3	Lens base: 9.75 curve	Hinge: polycarbonate + nylon
SB1830S	P + U6	P Z87 + / P c SEI Z94.3	Lens size diagonal: 56 mm	Screw: stainless steel
SB1835S	P + S	P Z87 + / P c SEI Z94.3	Lens size vertical: 45 mm	Side shields: polycarbonate
SB1840S	P + S	P Z87 + / P c SEI Z94.3	Lens thickness: 2.2 mm	Nosepiece: polycarbonate + thermoplastic rubbers (TPR)
SB1850SF	P + W5	P Z87 +	Overall length (lens - tip): 150-163 mm	
SB1860S	P + S	P Z87 + / P c SEI Z94.3	Overall width (hinge - hinge): 142 mm	
SB1860SF	P + W3	P Z87 +		
SB1870S	P + S	P Z87 + / P c SEI Z94.3		
SB1875S	P + S	P Z87 + / P c SEI Z94.3		
SB1880S	P + U6 L 1.7	P Z87 + / P c SEI Z94.3		
SB1880ST	P + U6 L 1.7	P Z87 + / P c SEI Z94.3		
SB1890S	P + S	P Z87 + / P c SEI Z94.3		
SMB1810S	P + U6	P Z87 +		
SMB1820S	P + U6 L 2.5	P Z87 +		
SMB1880S	P + U6 L 1.7	P Z87 +		
SSG1810S	P + U6	P Z87 +		

Lens Marking Symbols

P: Manufacturer's mark

+: High impact

S: Special Purpose

W: Welding filter

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light

L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

c SEI Z94.3: CAN/CSA standard for eye and face protection devices