



RUBBER
NOSEPIECE



ADJUSTABLE
TEMPLES



MIL-PRF-
32432



READER
OPTION



Venture II®

ANSI/ISEA Z87.1-2020 + | CAN/CSA Z94.3-20 |
CE/UKCA EN 166 | MIL-PRF-32432

Temples adjust to four different lengths // Rubber nose piece secures the glass and prevents slipping // Passes Ballistic MIL-PRF-32432 High Velocity Impact standards // Custom imprinting available

VARIATIONS

Black Frame | 13 Variations

	SB1810S	Clear
	SB1810ST	Clear H2X AF
	SB1820S	Gray
	SB1820ST	Gray H2X AF
	SB1830S	Amber
	SB1835S	Rust Bronze
	SB1840S	Orange
	SB1860S	Infinity Blue
	SB1870S	Silver Mirror
	SB1875S	Blue Mirror
	SB1880S	I/O Mirror
	SB1880ST	I/O Mirror AF
	SB1890S	Gold Mirror



RUBBER
NOSEPIECE



ADJUSTABLE
TEMPLES



MIL-PRF-
32432



READER
OPTION



Part No.	Lens Marking	Temple Marking	General Specifications	Materials
SB1810S	P + U6	P Z87 + / P c SEI Z94.3	Weight: 27 gm	Lens: Polycarbonate
SB1810ST	P + U6	P Z87 + / P c SEI Z94.3	PD: 68 mm	Frame: Nylon 6-6 - Poly (Hexamethylene Adipamide)
SB1820S	P + U6 L 2.5	P Z87 + / P c SEI Z94.3	Bridge: 10.5 mm	Temples: Polycarbonate & Thermoplastic Elastomers (TPE)
SB1820ST	P + U6 L 2.5	P Z87 + / P c SEI Z94.3	Lens Base: 9.75 curve	Hinge: Polycarbonate + Nylon
SB1830S	P + U6	P Z87 + / P c SEI Z94.3	Lens Size Diagonal: 56 mm	Screw: Stainless Steel
SB1835S	P + S	P Z87 + / P c SEI Z94.3	Lens Size Vertical: 45 mm	Side Shields: Polycarbonate
SB1840S	P + S	P Z87 + / P c SEI Z94.3	Lens Thickness: 2.2 mm	Nose Piece: Polycarbonate + Thermoplastic Rubbers (TPR)
SB1860S	P + S	P Z87 + / P c SEI Z94.3	Overall Length (lens - tip): 150-163 mm	
SB1870S	P + S	P Z87 + / P c SEI Z94.3	Overall Width (hinge - hinge): 142 mm	
SB1875S	P + S	P Z87 + / P c SEI Z94.3		
SB1880S	P + U6 L 1.7	P Z87 + / P c SEI Z94.3		
SB1880ST	P + U6 L 1.7	P Z87 + / P c SEI Z94.3		
SB1890S	P + S	P Z87 + / P c SEI Z94.3		

Lens Marking Symbols

P: Manufacturer's mark

+: High impact

S: Special Purpose

W: Welding filter

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light

L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

c SEI Z94.3: CAN/CSA standard for eye and face protection devices