



RUBBER
NOSEPIECE



ADJUSTABLE
TEMPLES



READER



Venture II® Readers

ANSI/ISEA Z87.1-2020 + | CAN/CSA Z94.3-20 |
CE/UKCA EN 166

Temples adjust to four different lengths // Rubber nosepiece secures the glass and prevents slipping // Custom imprinting available

VARIATIONS

Black Frame | 15 Variations

SB1810R10	Clear	+1.0 Mag	SB1880R15	I/O Mirror	+1.5 Mag
SB1810R15	Clear	+1.5 Mag	SB1880R20	I/O Mirror	+2.0 Mag
SB1810R15T	Clear H2X AF	+1.5 Mag	SB1880R25	I/O Mirror	+2.5 Mag
SB1810R20	Clear	+2.0 Mag			
SB1810R20T	Clear H2X AF	+2.0 Mag			
SB1810R25	Clear	+2.5 Mag			
SB1810R25T	Clear H2X AF	+2.5 Mag			
SB1810R30	Clear	+3.0 Mag			
SB1820R15	Gray	+1.5 Mag			
SB1820R20	Gray	+2.0 Mag			
SB1820R25	Gray	+2.5 Mag			
SB1820R30	Gray	+3.0 Mag			



Part No.	Lens Marking	Temple Marking	General Specifications	Materials
SB1810R10	P + U6	+1.00 P Z87 + / P c SEI Z94.3	Weight: 27 gm	Lens: Polycarbonate
SB1810R15	P + U6	+1.50 P Z87 + / P c SEI Z94.3	PD: 68 mm	Frame: Nylon 6-6 - Poly (Hexamethylene Adipamide)
SB1810R15T	P + U6	+1.50 P Z87 + / P c SEI Z94.3	Bridge: 10.5 mm	Temples: Polycarbonate & Thermoplastic Elastomers (TPE)
SB1810R20	P + U6	+2.00 P Z87 + / P c SEI Z94.3	Lens Base: 9.75 curve	Hinge: Polycarbonate + Nylon
SB1810R20T	P + U6	+2.00 P Z87 + / P c SEI Z94.3	Lens Size Diagonal: 56 mm	Screw: Stainless Steel
SB1810R25	P + U6	+2.50 P Z87 + / P c SEI Z94.3	Lens Size Vertical: 45 mm	Side Shields: Polycarbonate
SB1810R25T	P + U6	+2.50 P Z87 + / P c SEI Z94.3	Lens Thickness: 2.2 mm	Nose Piece: Polycarbonate + Thermoplastic Rubbers (TPR)
SB1810R30	P + U6	+3.00 P Z87 + / P c SEI Z94.3	Overall Length (lens - tip): 150-163 mm	
SB1820R15	P + U6 L 2.5	+1.50 P Z87 + / P c SEI Z94.3	Overall Width (hinge - hinge): 142 mm	
SB1820R20	P + U6 L 2.5	+2.00 P Z87 + / P c SEI Z94.3		
SB1820R25	P + U6 L 2.5	+2.50 P Z87 + / P c SEI Z94.3		
SB1820R30	P + U6 L 2.5	+3.00 P Z87 + / P c SEI Z94.3		
SB1880R15	P + U6 L 1.7	+1.50 P Z87 + / P c SEI Z94.3		
SB1880R20	P + U6 L 1.7	+2.00 P Z87 + / P c SEI Z94.3		
SB1880R25	P + U6 L 1.7	+2.50 P Z87 + / P c SEI Z94.3		

Lens Marking Symbols

P: Manufacturer's mark

+: High impact

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light

L2.5: 29% max visible light

Temple Marking Symbols

+1.00: magnification of +1.0

+1.50: magnification of +1.5

+2.00: magnification of +2.0

+2.50: magnification of +2.5

+3.00: magnification of +3.0

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

c SEI Z94.3: CAN/CSA standard for eye and face protection devices