# Auto-Darkening Helmet

Product Sheet



# WHAM30 Series

ANSI/ISEA Z87.1-2020 • CAN/CSA Z94.3-20 •

4/5-8/9-13 stepless variable shade // 3.858"x 3.425" (98 x 87 mm) view area // Manual internal controls // Four independent sensors in staggered design // Solar cells and replaceable lithium-battery // Cutting, grinding and welding modes // 1/30,000 second switch speed // 5 amps and below TIG rating // High-impact resistant nylon // Up to shade DIN 16 at all times

| Ø | WHAM3030AE•  | American Eagle |
|---|--------------|----------------|
| 1 | WHAM3030FL•• | Flame          |
| ۲ | WHAM3030FM•• | Fire Metal     |
|   | WHAM3030GB•• | Glossy Black   |

## **Replacement Cover Plates**

| R0WH3060PK5•• | Front cover plate WHAM30  |
|---------------|---------------------------|
| RIWH30PK5••   | Inside cover plate WHAM30 |

## **Replacement Filter**

WRAM30 • Auto Darkening Filter for WHAM30

Auto-darkening helmets are suitable for all types of electro-weldings: covered electrodes, MIG/MAG, TIG/WIG, plasma welding, cutting and laser welding (only selected models with two shade ranges, ie.5-8 and 9-13), except for gas welding. Pyramex recommends Duracell® DL2450 replacement lithium coin battery for WHAM30.






WHAM3030AE

WHAM3030FL

WHAM3030FM



Manual Controls

PYRAMEX<sup>®</sup> **¾ ₩ → ∧ 0 ⊕** ☆ ▲ P 800.736.8673 // F 901.861.4967 // W PYRAMEX.COM

#### FILTERS ONLY

| Cartrid                         | lge Size | Viewing A         | rea Shade Contr                 | rol                      | Welding Shade<br>Range | Cutting Shade<br>Range |                                    | h Speed<br>- Drk) |                      | lay Time<br>Ir - Drk) | ,                     | ustable<br>Delay | Numbers of<br>Sensors |                        |   |
|---------------------------------|----------|-------------------|---------------------------------|--------------------------|------------------------|------------------------|------------------------------------|-------------------|----------------------|-----------------------|-----------------------|------------------|-----------------------|------------------------|---|
| 114 x 13                        | 33x9 mm  | 98 x 87 m         | nm Internal - stepl<br>variable | ess                      | 9-13                   | 5 - 8 separate         | <1/3                               | 30000s            | ; 0.1 - 1.0s         |                       | 0.1 - 1.0s            |                  |                       | al-stepless<br>ariable | 4 |
| Adjustable<br>Sensitivity       |          | Grinding Function |                                 | Low Battery<br>Indicator | Back-up Batterie       |                        | ow Ampera<br>TIG Rating<br>(DC/AC) | <b>U</b>          | Switch S<br>(Clr - D |                       | Delay Ti<br>(Clr - Dı |                  |                       |                        |   |
| Internal - stepless<br>variable |          | Yes               |                                 | Yes                      | DL2450                 |                        | < 5 amps                           |                   | Auto                 |                       | ANSI Z87<br>2015      | -                |                       |                        |   |

#### HELMET ONLY

| Helmet Shell      | ANSI Certification | CSA Certification           | Impact Resistant | Flame Resistant | Operating Temp | Delay Time<br>(Clr - Drk) |
|-------------------|--------------------|-----------------------------|------------------|-----------------|----------------|---------------------------|
| High Impact Nylon | ANSI Z87.1-2020    | CAN/CSA Z94.3-20<br>Class 3 | Yes              | Yes             | 14°F - 140°F   | -4°F - 158°F              |

#### FULL PRODUCT (HELMET, HEADGEAR, FILTER)

| Weight | Front Lens Cover Qty | Packaging             |
|--------|----------------------|-----------------------|
| 560g   | 2                    | 1 per box   6 in case |

#### **Product Guarantee:**

Pyramex Safety Products guarantees the LEADHEAD line of the ADF welding helmets as follows:

The Auto Darkening filter is covered by a 2 year warranty. The welding helmet shell and headgear have a 90-day warranty.

All warranties begin on the day of purchase. Pyramex Safety does not cover damage resulting from user error or negligence. If you need repair or maintenance for your ADF, contact us at 1-800-736-8673.

PYRAMEX® 💘 🖬 🕶 🗛 🛛 🖓 🤹 🛤

P 800.736.8673 // F 901.861.4967 // W PYRAMEX.COM