


**XS3 PLUS®** ANSI • CSA •



Unique slim temple design with co-injected temple tips //  
 Flame resistant foam padding // Detachable strap // Passes  
 D3: Droplet and Splash Test // Custom imprinting available

**Black Frame | 2 Variations**

- SB4610STP •• Clear **H2X AF**
- SB4620STP •• Gray **H2X AF**



**General Specifications**

Weight: 34 gm  
 PD: 68 mm  
 Bridge: 19.3 mm  
 Lens base: 7 curve  
 Lens size diagonal: 131 mm  
 Lens size vertical: 50 mm  
 Lens thickness: 2.1 mm  
 Overall length (lens-tip): 155 mm  
 Overall width (hinge-hinge): 145 mm

**Materials**

Lens: polycarbonate  
 Frame: nylon 66  
 Strap: polyester  
 Nosepiece: polycarbonate  
 Temple: polycarbonate  
 Temple tips: thermoplastic elastomers  
 Sponge: chloroprene rubber  
 Hinge: polycarbonate  
 Screw: stainless steel

**Part No.**

SB4610STP  
 SB4620STP

**Lens Markings**

P Z87 + U6 D3  
 P Z87 + U6 L2.5 D3

**Frame Markings**

P Z87 + D3 / P c SEI Z94.3  
 P Z87 + D3 / P c SEI Z94.3

**Lens Marking Symbols**

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 D3: Droplet & Splash Test  
 UV Filter Transmittance  
 U6: .01% max effective far UV • .1% max near UV  
 Visible Light Filters  
 L1.7: 55% Max. Visible Light  
 L2.5: 29% max visible light

**Frame Marking Symbols**

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 D3: Droplet & Splash Test  
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices