PYRAMEX

FOAM PADDING | INCLUDES STRAP | CO-INJECTED TEMPLES | PASSES D3 DROPLET AND SPLASH TEST | REMOVABLE TEMPLE STRAP

XS3 PLUS®

ANSI/ISEA Z87.1-2020+ | CAN/CSA Z94.3-20

Unique slim temple design with co-injected temple tips // Removable, adjustable temple strap // Flame resistant foam padding // Passes D3: Droplet and Splash Test with and without the strap // Custom imprinting available



VARIATIONS

Black Frame | 2 Variations

- SB4610STP — Clear H2X AF
- SB4620STP — Gray H2X AF





General Specifications

Weight: 34 gm
PD: 68 mm
Bridge: 19.3 mm
Lens base: 7 curve
Lens size diagonal: 131 mm
Lens size vertical: 50 mm
Lens thickness: 2.1 mm
Overall length (lens-tip): 155 mm
Overall width (hinge-hinge): 145 mm

Materials

Lens: Polycarbonate
Frame: Nylon 66
Strap: Polyester
Nose Piece: Polycarbonate
Temple: Polycarbonate
Temple Tips: Thermoplastic Elastomers
Sponge: Chloroprene Rubber
Hinge: Polycarbonate
Screw: Stainless Steel

Part No.	Lens Markings	Frame Markings
SB4610STP	P Z87 + U6 D3	P Z87 + D3 / P c SEI Z94.3
SB4620STP	P Z87 + U6 L2.5 D3	P Z87 + D3 / P c SEI Z94.3

Lens Marking Symbols

P: Manufacturer's mark

Z87: ANSI/ISEA Z87.1-2020 standard for eye and face protection devices

+: High impact

D3: Droplet & Splash Test

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light

L2.5: 29% max visible light

Frame Marking Symbols

P: Manufacturer's mark

Z87: ANSI/ISEA Z87.1-2020 standard for eye and face protection devices

+: High impact

D3: Droplet & Splash Test

c SEI Z94.3: Certified for CAN/CSA Z94.3-20 standard for eye and face protection devices

Product markings may vary // Updated as of 11.26