PYRAMEX

Zone II® ANSI • CE •



RUBBER NOSE PIECE

RUBBER TIPS

Built-in rubber nose piece //
Rubber coated temple tips //
Custom imprinting available

Matte Black Frame | 4 Variations

SB3310E ••	Clear
SB3320E ••	Gray
SB3365E •	Ice Blue Mirror
SB3380E •	I/O Mirror

Silver Frame | 5 Variations

SS3320E ••	Gray
SS3345E •	Ice Orange Mirror
SS3365E •	Ice Blue Mirror
SS3370E •	Silver Mirror
SS3375E •	Blue Mirror



SS33

Part No.	Lens Marking	Temple Marking
SB3310E	P + U6	P Z87 +
SB3320E	P + U6 L2.5	P Z87 +
SB3365E	P + S	P Z87 +
SB3380E	P + U6 L1.7	P Z87 +
SS3320E	P + U6 L2.5	P Z87 +
SS3345E	P + S	P Z87 +
SS3365E	P + S	P Z87 +
SS3370E	P + S	P Z87 +
SS3375E	P + S	P Z87 +

General Specifications

Weight: 32 gm
PD: 68 mm
Bridge: 9 mm
Lens base: 9.5 curve
Lens size diagonal: 64 mm
Lens size vertical: 43.5 mm
Lens thickness: 2.4 mm
Overall length (lens - tip): 160.5 mm
Overall width (hinge - hinge): 136.5 mm
Closest point between lens: 87.0 mm

Materials

Lens: polycarbonate
Frame: nylon 66
Temples: polycarbonate
Temples tips: polyvinyl chloride
Hinge: polycarbonate & nylon
Screw: stainless steel
Nose Piece: polyvinyl chloride

Lens Marking Symbols

P: Manufacturer's mark

+: High impact

S: Special Purpose

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light

L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact